



SURFACE PREPARATION

CUB GRINDER ART-CUB

The Cub Grinder is compact in design and delivers exceptional grinding capability across a wide range of applications. With the weight of the motor sitting directly over the grinding head grinding efficiency is enhanced. Fitted with a direct drive coupling design there is no drive belts that require ongoing adjustments and timely maintenance.



Central lifting hook for easy and safe onsite handling.

Electric motor overload protection for complete safety.

Full compliance for use with standard 10A power outlet.

Fold over handles for easy transport and storage.

Adjustable handle height for user comfort.

Dust outlet for connection with vacuum system or tap for water connection for complete suppression of dust.

ART-CUB

Product & Performance Specifications

Cub Grinder

Model Number	ART-CUB	Power Output (Hp)	2.4
Grinding Width (mm)	250	Motor Speed (rpm)	1440
Operating Weight (kg)	46	IP Rating	55
Lifting Hook	Yes	Overload Protection	Yes
Voltage (volt)	240V	Product Code	FT1RTCUB-UNIT
Max Current (amp)	9.57A	Barcode	9330221020817
Power Output (kw)	1.8		

1300 353 986

www.flextool.com.au

Parchem Construction Supplies Pty Ltd
7 Lucca Road, Wyong NSW AUS 2259



Flextool®

SINCE 1951