

FLEXTOOL SINGLE HEAD CONCRETE GRINDER FCG-250

The Flextool Single Head Concrete Grinder FCG-250 is compact in design and delivers exceptional grinding capability. The combination of the direct drive system and the motor positioned directly over the grinding head, allow for efficient and aggressive grinding. Designed for professionals, the FCG-250 has a detachable grinding head for easier transportation, a folding handle with adjustable handlebar, easy access control panel and a central lifting hook.

The innovative floating grinding head with self-levelling pivot follows the floor profile, which promotes even wear of the grinding shoes. A floating dust shroud gives a tight seal, capturing harmful dust from escaping the grinding head.

Changing grinding shoes is fast and hassle-free with the Easy Lock tooling system. Compatible with the Redi Lock system, this machine comes standard with a grinding shoe adaptor plate.

This machine is ideal for small and medium domestic or commercial projects, where coating removal, levelling high spots, or general concrete grinding and surface preparation are needed.



Reversible with 3-way height adjustment for superior ergonomics

Lifting hook

Central lifting hook for easy and safe onsite handling

Single phase electric motor

1.8 kW electric motor for use with standard 10 amp power outlet

Direct drive system

Delivers optimum grinding efficiency with full motor weight directly

over the grinding head

Floating head

Self-levelling pivot follows the floor profile promoting even wear of the grinding

shoes and plates

Easy operator control

Control panel positioned within easy reach for optimised control and safety

Folding handle

3 locking positions for transport and storage, changing of consumables and operation

Detachable grinding head

Quickly and easily separate the grinding head and motor from the main chassis for easier handling, transportation and storage

Easy Lock grinding shoe adaptor plate included

- Fast and hassle-free changeover of grinding shoes
 - Compatible with universal Redi Lock system
- Can also be operated with 250 mm (10 inch) grinding plates

Dust management system

Equipped with dual shrouds (full seal and edge grinding), 50 mm vacuum port, and water inlet for ultimate dust control



PRODUCT & PERFORMANCE SPECIFICATIONS



FLEXTOOL SINGLE HEAD CONCRETE GRINDER



FCG-250

Model	Grinding Width mm (in)	Operating Weight kg (lb)	Voltage V/Hz	Max Current A	Power Output kW	Power Output hp	Grinding Speed rpm	IP Rating	Dust Outlet mm (in)	Lifting Hook	Grinding Shoes	Power Cord Length m (ft)	Product Code
FCG-250	250 (10)	76 (167.5)	240 50/60	9.8	1.8	2.4	1400	55	50 (2)	Yes	Easy Lock (Redi Lock Compatible)*	0.3 (1)	FT100601-UNIT

^{*} Adaptor plate included as standard

FLEXTOOL GRINDING CONSUMABLES

FLEXTOOL BLADETEC EASY LOCK GRINDING SHOES

Application	Colour	Bond Type	Number of Segments	Diamond Grit Size	Pack Qty	Product Code
		Hard Bond	2	16 grit	3	FT100473-UNIT
C-ft Ct-	Black			40 grit	3	FT100474-UNIT
Soft Concrete				80 grit	3	FT100475-UNIT
				100 grit	3	FT100476-UNIT
		Medium Bond		16 grit	3	FT100477-UNIT
Medium Hardness Concrete	Silver		2	40 grit	3	FT100478-UNIT
Medium Hardness Concrete	Silver			80 grit	3	FT100479-UNIT
				100 grit	3	FT100480-UNIT
	White	Soft Bond		16 grit	3	FT100481-UNIT
Hard Orange			2	40 grit	3	FT100482-UNIT
Hard Concrete				80 grit	3	FT100483-UNIT
				100 grit	3	FT100484-UNIT
	Gold	Very Soft Bond		16 grit	3	FT100485-UNIT
Very Head Occupie			1	40 grit	3	FT100486-UNIT
Very Hard Concrete				80 grit	3	FT100487-UNIT
				100 grit	3	FT100488-UNIT
Thick Coatings (Epoxy, Glue)	D-d	PCD	3	N/A	3	FT100489-UNIT
Thin Coatings (Paint, Sealant)	Red	Soft Bond	2	16 grit	3	FT100490-UNIT













FLEXTOOL BLADETEC GRINDING PLATE

Application	Diameter mm (in)	Colour	Bond Type	Number of Segments	Diamond Grit Size	Pack Qty	Product Code
General Purpose Concrete Grinding	250 (10)	White	Soft Bond	15	30/40 grit	1	FT100472-UNIT





Version 2.0 (Septern