

MIKASA FLOOR AND ROAD SAW MCD-T18H-PLUS

The Mikasa Floor and Road Saw MCD-T18H-PLUS sets the standard in precision cutting. Featuring a Honda GX390 engine with cyclonic air filtration system and anti-vibration adjustable handle, it ensures optimum performance and operator comfort. The uniquely designed water pump injection system prevents loss of water pressure and provides consistent water flow for effective dust suppression, while a cutting depth gauge and superior power transmission enhance cutting accuracy. This saw is ideal for a variety of cutting applications in concrete and asphalt.

Anti-vibration and adjustable handle

- Low vibration handle for reduced hand and arm vibration transfer to the operator
- Height-adjustable handle for improved operator comfort

Cutting depth gauge with lock

Equipped with depth control cutting gauge and locking mechanism to ensure precise and accurate cutting and enhance operator safety

Lifting hook

Central lifting hook for easy and safe onsite handling

Cyclonic air filtration system

For superior air filtration to lengthen service intervals and improve engine protection

Engine hour meter and tachometer

Efficiently manage service intervals

50 Litre integrated water tank

Large integrated water tank for extended operation

Safety brake

Easy to operate foot brake to prevent unwanted movement during operation and transport

Water pump injection system

Uniquely designed water injection system which provides consistent water application, ensuring no loss of water pressure throughout the entire cutting process for superior dust suppression

Blade guard

Fully removable, ultra-lightweight aluminium blade guard for quick and easy access when changing blades

Honda GX390 engine

Provides hassle free operation and low engine emissions

Superior power transmission

Special wide profile banded drive belt for maximum power transfer to the cutting blade

Sealed pulley and belt guard

Protects against the ingress of dust and other unwanted materials that can prematurely wear out pulley and drive belt components



POWERED by
HONDA

MIKASA FLOOR AND ROAD SAW



Model	Operating Weight (kg)	Blade Size mm (in)	Max Cutting Depth (mm)	Lifting Hook	Water Tank Capacity (L)	Engine Make	Engine Model	Max Rated Power (hp)	Fuel Type	Product Code
MCD-T18H-PLUS	133	460 (18")	170	Yes	50	Honda	GX390	13		FT201693-UNIT

Version 3.0 (March 2025)

EXCLUSIVE TO



This Technical Data Sheet (TDS) summarises our best knowledge of the product, based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use of the product whether or not in accordance with any advice, specification, recommendation or information given by it.

© This publication is copyright. All rights are reserved. Flextool is a registered trade mark of Parchem Construction Supplies Pty Ltd. Mikasa is a registered trade mark of Mikasa Sangyo Co. Ltd, used under licence.